

Advanced Fluid Systems, Inc.

Fluid Power Distributor and Systems Manufacturer

Contact Us:

By Phone: 717-757-1068

sales@advancedfluidsystems.com

Hy-Pro Filtration's VAC-U-DRY portable vacuum dehydrators are an economical solution for quickly removing water, gas and particulate contamination from your lube, transformer and hydraulic fluids.



V20 VAC-U-DRY Purifier Stats:

Model: V20
Dimensions (in.): 72L x 36W x 60H
Weight (crated): 2,100 lbs.
Electrical Service: 460VAC, 3P, 60Hz
Flow Rate: 5 to 20 GPM
Reservoir Volume: 100 to 6000 Gal.

Water removal rates and graphs are available in the VAC-U-DRY literature at our website or at www.hyprofiltration.com

V20 VAC-U-DRY Rental Pricing

V20 Rental Pricing	
Rental Period	Rate
Per Month	\$ 5,100
Per Week	\$ 1,342
Each Add. Day	\$ 202

Minimum 3 Day Rental

VAC-U-DRY Element Pricing:

Each V20 VAC-U-DRY rental requires the purchase of (1) particulate filter and (4) vacuum dispersal elements. Additional elements may be required based on the fluid condition and length of operation. Contact us to determine the best elements for your fluid and application.

"Standard" Elements:

HP107L36-6MV Particulate element x (1) = \$423.00
 HPDEL22 Dispersal elements (set of 4) = \$588.00

** There is a \$500 security deposit for the purifier and crate for each rental.

Water Removal: 100% Free
 90%+ Dissolved
 (20 ppm / .0020%)

Air and Gas Removal: 100% Free
 90% Dissolved

Particulate Removal: ISO 14/12/9
 2.5m @ β1000

Worry-Free Operation: Dual condensate water tanks with automatic drain standard for 24 x 7 unattended operation.

Easy Setup: Automatic electric phase reversal; programmable thermostat; and smart relays with controlled start-up and shut down routines.

Free Support: On-site setup and start-up support is included free of charge on rentals in the Mid-Atlantic and New England regions.

Hydraulic Purifier Rental

...Quickly and safely remove water, gases and particulate.

The V1 series of vacuum dehydrator from Hy-Pro offers the same water, gas and particulate removal performance of its larger cousins, but in a smaller ultra-portable package. It's .5 to 1.8 GPM flow rate is ideal for quickly purifying smaller volumes of fluid and servicing multiple systems on a regular basis.

V1 VAC-U-DRY Rental Pricing

V1 Rental Pricing	
Rental Period	Rate
Per Month	\$ 1,580
Per Week	\$ 416
Each Add. Day	\$ 63

Minimum 3 Day Rental

VAC-U-DRY Element Pricing:

Each V1 VAC-U-DRY rental requires the purchase of (1) particulate filter and (1) vacuum dispersal element. Additional elements may be required based on the fluid condition and length of operation. Contact us to determine the best elements for your fluid and application.

"Standard" Elements:

HP76L8-3MV Particulate element = \$ 77.00
 HPDEL11 Dispersal elements = \$102.00

** There is a \$500 security deposit for the purifier and crate for each rental.

V1 VAC-U-DRY Purifier Stats:

Model: V1
Dimensions (in.): 48L x 28W x 32H
Weight (crated): 425 lbs.
Electrical Service: 120VAC, 60Hz
Flow Rate: .5 to 1.8 GPM
Reservoir Volume: up to 300 Gal.

Water removal rates and graphs are available in the VAC-U-DRY literature at our website or at www.hyprofiltration.com



Visit us online at: www.advancedfluidsystems.com

Advanced Fluid Systems, Inc.

Fluid Power Distributor and Systems Manufacturer

The VAC-U-DRY Purification Process:

Contaminated oil is drawn into the VAC-U-DRY purifier by a high output vacuum pump. The oil passes through the low watt density heater where it is heated to optimum temperature for the dehydration process (150°F, 66°C). The oil enters the vacuum chamber passing through specially designed dispersal elements which create a thin film of oil that is exposed to the vacuum. The water is vaporized and then

Contaminant Type	VAC-U-DRY Capability
Water	Remove 100% free water 90% + dissolved water
Particulate	ISO Cleanliness Code 13/11/8 per ISO4406:1999
Gases	Remove 100% free gases 90% + dissolved gases
Air	Remove 100% free air 90% + dissolved air

drawn into the condenser where it becomes liquid and drains into the condensate tank. The dehydrated oil flows to the bottom of the vacuum chamber and is pumped through the high efficiency particulate filter assembly and returned to the system.

Contact us for a free consultation and see if a Hy-Pro VAC-U-DRY vacuum dehydrator is right for you.

Other Filtration Systems from Hy-Pro...

SVR Varnish Removal System: Remove free and dissolved oil varnish and particulate contamination, reducing acidity (TAN) to normal levels without removing critical oil additives.

CO Coalesce Skids: Remove free water and dissolved water to 150 PPM in turbine lube oil and 75 PPM in diesel fuel, while removing particulate.

FSL Filtration Skids:

Dedicated filtration for gearbox, kidney-loop, fluid transfer and high viscosity applications.



FCL Filtration Cart: Mobile version of the FSL filtration skid, the FCL cart features wheels and a retractable power cord.

FC Filter Cart: Portable filtration system on a two wheeled hand-cart. Ideal for transferring new fluid and conditioning oil before use.

FPL Spin-on Filter Panel: Mounted filtration panel ideal for filtering replenishment (top-off) fluid or as a kidney-loop adder for existing applications.

On-site Particulate Counting and Identification - Detailed 3rd-Party Fluid Analysis - Custom Filtration Systems

3rd Party Fluid Analysis and Reporting

The Hy-Pro OA1 fluid analysis kit is an inexpensive, prepaid 3rd-party oil analysis tool that is independently tested and reported by Analysts, Inc. Results are fast, accurate and available online or by mail. The kit includes a sterile bottle and paperwork and may be used at any time.

Test results include:

- ISO 4406:1999 Particle Count 4/6/14
- 21 Element Spectrometric Analysis
- TAN (Total Acid Number)
- Water Content PPM
- (Colorimetric Varnish Potential Testing Available)




Order Part#: OA1
\$53.85 Net Each

Advanced Fluid System's custom filtration systems allow you to clean and condition your system's fluid regardless of the system's operation or location. Examples include mobile filter carts, fluid transfer carts and high flow filter skids.

Some filtration characteristics include:

- Particulate filtration down to 1 micron absolute at beta ratio 200 (3 micron absolute at beta ratio 1000).
- Filtration and control solutions for a variety of fluids including hydraulic, lube oil, process water and hazardous fuels and chemicals.
- Optional integrated particle counters and water sensors that report fluid quality in real-time.
- Custom user interfaces, PLC design and operator controls for automated start-up and shut-down sequences, and worry-free operation.



York, PA:

PO Box 3342
245 Campbell Rd.
York, PA 17402

717-757-1068 Phone
717-757-4915 Fax

Royersford, PA:

PO Box 360
292 Green St.
Royersford, PA 19468

610-948-1000 Phone
610-948-1010 Fax

Glen Burnie, MD:

PO Box 786
899C Airport Park Rd
Glen Burnie, MD 21061

800-606-9801 Phone
410-553-0316 Fax

sales@advancedfluidsystems.com

Visit us online at: www.advancedfluidsystems.com